





絶縁被覆付圧着端子 (AVAP・APAP/BVAP・BPAP形)



板状形端子

形状	呼び		在庫	呼び	在庫	タイプ	各部の寸法							標準色	適合電線範囲			適合工具	一箱入数					
	UL	CSA					ピニル	CSA	ナイロン	B	d ₁		F ₁		l ₂	l	L ₁			板厚	H	単線mm	撚線mm ²	AWG
											BV	BP												
ストレート形			AVAP-0.5				1.6	2.2	-	7.0	11.0	16.5	0.5		黄	0.6~0.8	0.3~0.5	22-20	DS05N DH-1B	1,000				
			AVAP-1.25S				1.0			9.7	14.0	19.2			赤	0.8 ∩ 1.44	0.5 ∩ 1.65	20-16	3号D 34号 34S DH-1B AC-5N-D	500				
			AVAP-1.25				3.1			12.7	17.0	22.2												
			AVAP-1.25-9				2.1	3.3	9.0	13.3	18.5													
			AVAP-1.25-9B				3.1			10.2	14.5	19.7			青	1.14 ∩ 1.82	1.04 ∩ 2.63	16-14	4号D 34号 34S DH-1B AC-5N-D					
			AVAP-1.25-9B				2.1			16.7	21.0	26.2	0.8											
			AVAP-1.25-10				2.1			10.2	14.5	19.7												
			AVAP-1.25L				3.1			12.7	17.0	22.2			黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D					
			AVAP-2				2.1	3.9	9.0	13.3	18.5													
			AVAP-2-9				3.1			16.7	21.0	26.2												
			AVAP-2-9B				3.1			12.7	17.0	22.2			黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D					
			AVAP-2L				2.1			16.7	21.0	26.2												
		AVAP-2LB				3.2			12.7	17.0	22.2													
		AVAP-5.5				3.3	5.4	14.4	14.0	20.7	28.4	1.0	-	黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D						
		AVAP-5.5L				4.5			18.2	24.5	32.2													
		AVAP-5.5B				4.5			13.0	19.3	27.0													
拡管形			BVAP-0.5				1.6	3.2	-	7.0	11.0	16.0	0.5		黄	0.6~0.8	0.3~0.5	22-20	DS05N DH-1B	1,000				
			BVAP-1.25S				1.0			9.7	14.0	18.7			赤	0.8 ∩ 1.44	0.5 ∩ 1.65	20-16	3号D 34号 34S DH-1B AC-5N-D					
			BVAP-1.25				3.1			12.7	17.0	21.7												
			BVAP-1.25-9				2.1	4.1	4.0	9.0	13.3	18.0												
			BVAP-1.25-9B				3.1			10.2	14.5	19.2			青	1.14 ∩ 1.82	1.04 ∩ 2.63	16-14	4号D 34号 34S DH-1B AC-5N-D					
			BVAP-1.25-9B				2.1			16.7	21.0	25.7	0.8											
			BVAP-1.25L				2.1			10.2	14.5	19.2												
			BVAP-2				3.1			12.7	17.0	21.7			黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D					
			BVAP-2-9				2.1	4.7	4.5	9.0	13.3	18.0												
			BVAP-2-9B				3.1			16.7	21.0	25.7												
			BVAP-2L				2.1			12.7	17.0	21.7			黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D					
			BVAP-2LB				3.2			12.7	17.0	21.7												
		BVAP-5.5				3.3	6.4	-	14.4	20.7	27.9	1.0	-											
		BVAP-5.5L				4.5			18.2	24.5	31.7			黄	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5号 DH-1B AC-5N-D						
		BVAP-5.5B				4.5			13.0	19.3	26.5													
		BVAP-5.5B				4.5			13.0	19.3	26.5													
ストレート形			AVAP-1.25TU				3.0	3.3		13.2	9.5	21.5	26.7	0.8	1.8	赤	0.8 ~1.44	0.5 ~1.65	20-16	(注1)	500			
			AVAP-2TU				3.0	3.9		13.2	9.5	21.5	26.7	0.8	1.8	青	1.14 ~1.82	1.04 ~2.63	16-14	(注2)				
拡管形			BVAP-1.25TU				3.0	4.1	4.0	13.2	9.0	21.5	26.2	0.8	1.8	赤	0.8 ~1.44	0.5 ~1.65	20-16	(注1)	500			
			BVAP-2TU				3.0	4.7	4.5	13.2	9.0	21.5	26.2	0.8	1.8	青	1.14 ~1.82	1.04 ~2.63	16-14	(注2)				

- 各呼びの印は、UL登録品、CSA登録品です。
- UL登録品又は、CSA登録品としてご使用の際は、注文時にご指示ください。カートンがUL品用又はCSA品用となります。

(注1) 3号D, 34号, 34S, DH-1B, AC-5N-D (注2) 4号D, 34号, 34S, DH-1B, AC-5N-D

板状形端子は通常の電流よりも60%~70%位の目安でご使用ください。